

## DATASHEET

---

The single-use concept of aScope 4 Broncho once and for all solves the problem of accessibility, simplifies set-up for procedures, eliminates the need for complex cleaning procedures and minimizes the risk of cross-contamination. It comes sterile straight from the pack, offering improved patient safety and workflow.

The aScope 4 Broncho Regular offers high quality bronchoscopy for a broad range of procedures. When connected to Ambu aView™ 2 Advance, aScope 4 Broncho Regular gives you clear visibility of the near and distal bronchial segments. The clear, sharp images and adaptive light control make identification of lung anatomy and navigation in the bronchial tree easy.

The high bending angles and precise tip motion of aScope 4 Broncho Regular allows you to easily navigate into all segments of the lung. The high quality handle is designed with a shaped, rippled surface to provide a comfortable grip throughout the procedure. The lightweight and ergonomic design makes aScope 4 Broncho Regular easy to use.

The aScope 4 Broncho Regular has a working channel that is ideal for a wide range of bronchoscopy procedures. This ranges from intubation and training of intubation skills to bedside bronchoscopy including BAL & PDT procedures.

# Ambu® aScope™ 4 Broncho Regular 5.0/2.2

Guaranteed sterility, ready when you are



## KEY BENEFITS

---

Instant availability

No risk of cross-contamination

Cost effective

High degree of usability

Clear, sharp images

Smooth and easy navigation

World's first single-use bronchoscope with bioplastic handle

## SPECIFICATIONS

### Optical system

Field of View	85°
Direction of View	0° (forward viewing)
Depth of Field	6 - 50 mm
Illumination method	2 LEDs

### Insertion portion

Bending section	180° up, 180° down
Insertion cord diameter	5.0 mm (0.20")
Distal tip diameter	5.4 mm (0.21")
Maximum diameter of insertion portion	5.5 mm (0.22")
Minimum endotracheal tube size (inner diameter)	6.0 mm
Minimum double lumen tube size (inner diameter)	41 Fr
Working length	600 mm (23.6")

### Channel

Average inner diameter	2.2 mm (0.087")
Minimum instrument channel width*	2.0 mm (0.079")

### Suction connector

Connecting tube inner diameter range	6.5 mm - 9.5 mm
--------------------------------------	-----------------

### Storage

Temperature**	10 - 25 °C (50 to 77 °F)
Relative humidity	10 - 85 %
Atmospheric pressure	50 - 106 kPa

### Transportation

Temperature	-10 - 55 °C (14 to 131 °F)
Relative humidity	10 - 95 %
Atmospheric pressure	50 - 106 kPa

### Operating environment

Temperature	10 - 40 °C (50 to 104 °F)
Relative humidity	30 - 85 %
Atmospheric pressure	80 - 106 kPa
Altitude	≤ 2000 m

### Sterilisation

Method of sterilisation	ETO
-------------------------	-----

### Sustainability

Handle material	Bio-attributed ABS plastic
-----------------	----------------------------

## ORDERING SPECIFICATIONS

Item no.	Quantity/box	Transportation quantity
477001000	5	20

\* There is no guarantee that accessories selected solely using this minimum instrument channel width will be compatible in combination.

\*\* Storage under higher temperatures may impact shelf life.



Learn more about Ambu's sustainability initiatives:  
<https://www.ambu.com/endoscopy/single-use-endoscopy/environment>



**Ambu A/S**  
 Baltorpbakken 13  
 2750 Ballerup  
 Denmark  
 T +45 72 25 20 00  
 ambu.com



**Ambu aScope 4 Broncho Large and Ambu aView 2 Advance Next Gen**



**Ergonomic and lightweight handle designed to give you a firm and comfortable grip**