DATASHEET

The single-use concept of aScope 4 Broncho once and for all solves the problem of accessibility, simplifies set-up for procedures, eliminates the need for complex cleaning procedures and minimizes the risk of cross-contamination. It comes sterile straight from the pack, offering improved patient safety and workflow.

The aScope 4 Broncho Large offers high quality bronchoscopy for a broad range of procedures. When connected to Ambu aView[™] 2 Advance, aScope 4 Broncho Large gives you clear visibility of the near and distal bronchial segments. The clear, sharp images and adaptive light control make identification of lung anatomy and navigation in the bronchial tree easy.

The high bending angles and precise tip motion of aScope 4 Broncho Large allows you to easily navigate into all segments of the lung. The high quality handle is designed with a shaped, rippled surface to provide a comfortable grip throughout the procedure. The lightweight and ergonomic design makes aScope 4 Broncho Large easy to use.

The aScope 4 Broncho Large has a working channel that is ideal for a wide range of bronchoscopy procedures, including BAL & BW procedures.

Ambu® aScope™ 4 Broncho Large 5.8/2.8

Guaranteed sterility, ready when you are



KEY BENEFITS

Instant availability No risk of cross-contamination Cost effective High degree of usability Clear, sharp images Smooth and easy navigation World's first single-use bronchoscope with bioplastic handle



SPECIFICATIONS

Optical system	
Field of View	85°
Direction of View	0° (forward viewing)
Depth of Field	6 - 50 mm
Illumination method	2 LEDs
Insertion portion	
Bending section	180° up, 160° down
Insertion cord diameter	5.8 mm (0.23")
Distal tip diameter	6.3 mm (0.25")
Maximum diameter of insertion portion	6.3 mm (0.25")
Minimum endotracheal tube size (inner diameter)	7.0 mm
Minimum double lumen tube size (inner diameter)	-
Working length	600 mm (23.6")
Channel	
Average inner diameter	2.8 mm (0.110")
Minimum instrument channel width*	2.6 mm (0.102")
Suction connector	
Connecting tube inner diameter range	6.5 mm - 9.5 mm
Storage	
Temperature**	10 - 25 °C (50 to 77 °F)
Relative humidity	10 - 85 %
Atmospheric pressure	50 – 106 kPa
Transportation	
Temperature	-10 - 55 °C (14 to 131 °F)
Relative humidity	10 - 95 %
Atmospheric pressure	50 - 106 kPa
Operating environment	
Temperature	10 - 40 °C (50 to 104 °F)
Relative humidity	30 - 85 %
Atmospheric pressure	80 - 106 kPa
Altitude	≤ 2000 m
Sterilisation	
	FTO
Method of sterilisation	ETO
Method of sterilisation Sustainability Handle material	Bio-attributed ABS plastic



Ambu aScope 4 Broncho Large and Ambu aView 2 Advance Next Gen

Ergonomic and lightweight handle designed to give you a firm and comfortable grip

ORDERING SPECIFICATIONS

ltem no.	Quantity/box	Transportation quantity
478001000	5	20

* There is no guarantee that accessories selected solely using this minimum instrument channel width

will be compatible in combination. ** Storage under higher temperatures may impact shelf life.



Learn more about Ambu's sustainability initiatives: https://www.ambu.com/endoscopy/single-use-endoscopy/environment



Ambu A/S

Baltorpbakken 13 2750 Ballerup Denmark T +45 72 25 20 00 ambu.com