DATASHEET

aScope 5 Broncho combines the high level of manoeuvrability and imaging needed in the bronchoscopy suite with the sterility and efficiency of the singleuse concept. The result? Consistently high performance, sterility, and the flexibility required for a complex and demanding workflow.

Single-use like you've never seen it before

Ambu takes single-use bronchoscopy to even greater heights with our 5th generation of aScope Broncho. Building on over a decade of single-use bronchoscopy know-how, aScope 5 Broncho combines the familiar benefits of reusable scopes with the advantages of the single-use solution.

It is compatible with the full HD resolution Ambu[®] aBox[™] 2 and Ambu[®] aView[™] 2 Advance displaying and processing units and can easily be connected to external monitors.

aScope 5 Broncho delivers consistently high performance with excellent manoeuvrability, next-level imaging and a smart, functional design. This level of performance is complemented by the sterility and efficiency of the Ambu single-use solution to give you the quality and flexibility you need for a complex and demanding workflow in the bronchoscopy suite.

The aScope 5 Broncho is the world's first single-use bronchoscope with bioplastic in the handle. The ABS plastics used in our bronchoscope handle will now have a 70 % lower carbon footprint compared to traditional fossil-based plastic.

Ambu® aScope™ 5 Broncho HD 5.0/2.2



KEY BENEFITS

Completely eliminate the need for reprocessing and endoscope repairs

Start or expand bronchoscopy services with minimal capital investment

Easily navigate the bronchial segments with bending angles of 195°/195° (up/down)

Designed for smooth insertion and positioning of endotherapy instruments

Choose the right endotherapy instrument needed without fear of damaging an expensive scope

Visualize the bronchial tree clearly with the HD system delivering superior image quality

Seamlessly integrate Ambu displaying and processing units to the documentation systems in use

Offer your patient a sterile scope and eliminate the risk of patient-to-patient cross-contamination



SPECIFICATIONS

Optical system		
Field of View	120°	
Direction of View		
Depth of Field	0° (forward viewing) 3 - 100 mm	
- 1		
Illumination method Camera sensor module	LED CMOS	
	CMIOS	
Insertion portion		
Bending section	195° up, 195° down	
Insertion cord diameter	5.0 mm (0.20")	
Distal tip diameter	5.4 mm (0.21")	
Maximum diameter of insertion portion		
Minimum endotracheal tube size (inner diameter)	6.0 mm/18 Fr	
Working length	600 mm (23.6")	
Rotary function	120° left/right	
Depth marks	Every 5 cm	
Working channel		
Instrument channel width	2.2 mm (0.9")	
Minimum instrument channel width*	Min. Ø 2.05 mm (0.08")	
Suction connector		
Connecting tube inner diameter	Ø 5.5 - 9.0 mm	
Storage		
Temperature**	10 - 25 °C (50 to 77 °F)	
Relative humidity	10 - 85 %	
Atmospheric pressure	50 - 106 kPa	
Transportation		
Temperature	-10 - 55 °C (14 to 131 °F)	
Relative humidity	10 - 95 %	
Atmospheric pressure	50 - 106 kPa	
Operating environment		
Temperature	10 - 40 °C (50 to 104 °F)	
Relative humidity	30 - 85 %	
Atmospheric pressure	80 - 106 kPa	
Altitude	≤ 2000 m	
Sterilisation		
Method of sterilisation	ETO	
Sustainability		
Handle material	Bio-attributed ABS plastic	
Other		
	High frequency and the rany instruments	
Compatibility	High-frequency endotherapy instruments, argon plasma coagulation (APC) probes, cryobiopsy probes, Nd-YAG laser probes	
Latex and phthalate free	Yes	



aScope 5 Broncho HD 5.0/2.2 works with the full HD resolution Ambu® aBox[™] 2 and Ambu[®] aView[™] 2 Advance displaying and processing units and can easily be connected to external monitors.



aScope 5 Broncho HD 5.0/2.2 is compatible with endotherapy instruments designed to fit a working channel diameter of up to 2.2 mm.

ORDERING SPECIFICATIONS

ltem no.	Product name	Quantity
621001000	Ambu® aScope™ 5 Broncho HD 5.0/2.2	5

* There is no guarantee that accessories selected solely using this minimum instrument channel width

will be compatible in combination. ** Storage under higher temperatures may impact shelf life.



Mambu A/S Baltorpbakken 13 2750 Ballerup Denmark +45 72 25 20 00 Т ambu.com

